

Manufacturer: **Artisan Craft (Bd) Ltd**

Type: **Mechanical Induced Draft Counter Flow Bottle Type Cooling Tower**

Model: **ART-250**

- Heat Rejection: 1163 KW
- Water Flow Rate: 200 m<sup>3</sup>/h
- Water Intlet Temp: 37 °C
- Water Outlet Temp: 32 °C
- Wet Bulb Temp: 29 °C
- Range Temp: 5 °C
- Approach: 3 °C
- Evaporation Loss : 0.83%
- Drift Loss: <0.01%
- Make-up Water : <1.5%
- Noise Level: 70.5 dB (A)
- Inlet Water Pressure Head: 40 Kpa

**DESIGN & PARAMETERS**

**MATERIAL OF CONSTRUCTION**

- Basin: FRP
- Casing: FRP
- Access Door: NIL
- Fan Stack: NIL
- Distribution Basin: NIL
- Louver: NIL
- In-fill: PVC
- Eliminator: FRP
- Hardwares: H.D.G.S
- Ladder: H.D.G.S
- Safety Cage : NIL
- Safety Guard Rail: NIL
- Bolts & Nuts: H.D.G.S

- Type of Fan: Axial
- Fan Diameter : 2360 mm
- Fan Speed: 475
- No. of Fan Blade: 4
- MOC Fan Blade: Al
- Air Flow Rate: 103800 m<sup>3</sup>/h
- Motor Type: TEFC
- Motor Rating: 5.5 KW
- Pole No: 4
- Motor Rpm: 1440
- Voltage/Phase/Hz: 380V/3 Phase/50Hz
- Ingress Protection Rating: IP55
- Insulation: Class F

**FAN ASSEMBLY & MOTOR**

**WATER DISTRIBUTION SYSTEM**

- Sprinkler Distribution System
- Inlet Pipe: DN200
- Outlet Pipe: DN200
- Flaot Valve: DN25
- MakeUp: DN25
- Overflow: DN80
- Drain: DN40

- Diameter:3700mm
- Height:2860 mm
- Dry weight: 1475 Kg
- OperatingWeight: 3180 Kg

**PHYSICAL DATA**