Artisan Craft (Bd) Ltd.
We come when Temperature matters
www.artisan-craft.com

Manufacturer: **Artisan Craft (Bd) Ltd**

Type: **Mechanical Induced Draft Counter Flow Bottle Type Cooling Tower**

Model: **ART-80**

DESIGN & PARAMETERS

- Heat Rejection: 355 KW
- Water Flow Rate: 56 m3/h
- Water Intlet Temp: 37 °C
- Water Outlet Temp: 32 °C
- Wet Bulb Temp: 29 °C
- Range Temp: 5 °C
- Approach: 3 °C
- Evaporation Loss : 0.83%
- Drift Loss: <0.01%
- Make-up Water: <1.5%
- Noise Level: 70.5 dB (A)
- Inlet Water Pressure Head: 40 Kpa

MATERIAL OF CONSTRUCTION

- Basin: FRP
- Casing: FRP
- Access Door: NIL
- Fan Stack: NIL
- Distribution Basin: NIL
- Louver: NIL
- In-fill: PVC
- Eliminator: FRP
- Hardwares: H.D.G.S
- Ladder: H.D.G.S
- Safety Cage : NIL
- Safety Guard Rail: NIL
- Bolts & Nuts: H.D.G.S

FAN ASSEMBLY & MOTOR

- Type of Fan: Axial
- Fan Diameter : 1480 mm
- Fan Speed: 550
- No. of Fan Blade: 4
- MOC Fan Blade: Al
- Air Flow Rate: 27100 m^3/h
- Motor Type: TEFC
- Motor Rating: 4 KW
- Pole No: 10
- Motor Rpm: 550
- Voltage/Phase/Hz: 380V/3 Phase/50Hz
- Ingress Protection Rating: IP55
- Insulation: Class F

WATER DISTRIBUTION SYSTEM

- Sprinkler Distribution System
- Inlet Pipe: DN100
- Outlet Pipe: DN100
- Flaot Valve: DN20
- MakeUp: DN25
- Overflow: DN40
- Drain: DN25

PHYSICAL DATA

- Diameter: 2100mm
- Height: 2440 mm
- Dry weight: 430 Kg
- OperatingWeight: 790 Kg